DOI Number: 10.5958/0976-5506.2018.02084.3

Toxic Gases Identifying in Industries with Alert System using IoT

M.S.Varma[1], N Leelavathi[2], Sirisha Sangamitra[3], Venkateswara Kiran[2]

[1]Associate Professor, Department of CSE, [2]Assistant Professor, Department of CSE, [3]Associate Professor, Department of HBS, Godavari Institute of Engineering & Technology, Rajahmundry, A.P, India

ABSTRACT

Industries disasters are the purpose for the increasing unreliability in the human life particularly to the workers. To decrease these industries disasters, we developed a gadget that might recognize the poisonous gas and other physical condition utilizing the Internet of things (IoT). This project planned to avoided industries accident and checking the contamination control board. A central microcontroller is joined with sensors like shoot sensor, temperature, gas sensor. Sensors would be used to get the information from the environment at the leakage time. This will be utilized with single or multi dangerous gasses leakage that provides the fast result and response time is also high. An alarm may be used to generate a sound signal alert by industries to the nearby area living humans. If assume the level of the gasses and temperature goes above the average level than the indicated values than the alert will be provided for utilizing the internet of the web page and the android app which is created. Firstly, when the framework is developed we make one web page and an android app. Several numbers of clients who have a security ID (password) might see the information about temperature and gases leakages is an included principle advantage. This information of the sensors is stored on the internet in the equivalent website that could make utilized for future and further processing, and this will be good begin for industries to secure the humans in the surroundings and guarantee them a secured existence.

Keywords— *Microcontroller, gas sensors, fire sensor, temperature sensor, Wi-Fi module, internet of things, Website, android app.*

www.IJour.net
Members Copy, Not for Commercial Sale
Downloaded From IP - 18.222.125.171 on dated 29-Apr-2024

INTRODUCTION

This device is utilizing the limited radiation sensor and limited gas sensor; these sensors are collecting the transmitted information to the IoT module. Detection of toxic gas and leakage of radiation is the primary purpose of the overall device. In case any radiation leakages or poison gases are present in industrial areas, nearby living peoples are more affected by these gases or radiations. Continuous breathing of particular poisonous gases into the human body leads to death. The gases which are odorless are exposed to the environment for a long time causing various health issues. Depends upon based different gases and radiation detection, this device chooses of gases and radiation in devices like CO, ammonia, methane & infrared radiation. The "carbon-monoxide" is odorless that with above 150ppm concentration cause disorientation confusion, nervous damage, coma and fainting, and it will surely kill the human being. Every gas has its individual physical and chemical properties that make them complicated to investigate without any device[1,2] Poisonous gases exist in several phases based on the density and concentration of it. Gas sensor is working like gas molecule to absorb the gas sensor generated heat that heat converts into the electrical signal. Initially sensor detects a small amount of gas leakage. After the leakage amount is large go the harmful condition is high means produced an electrical signal to the Arduino board. Radiation sensor working like it measured the number of counts striking per minute detected by radiation sensor. The temperature sensor is sensing the condition of room temperature. These sensor gathering data send to an ARM board. ARM microcontroller already programmed that program operation based on gases and radiation monitoring level detection. Suppose getting sensor value level is high means inboard one pin connected to alarm it produces sound alert by industries people[3] . the

nearest fire station, police station. This indication based on saved industries surrounding people life move safe place. The LCD display it used to show any seepage occurring time indication display. The ARM7[11] board receiving information transferred to Wi-Fi module or Ethernet module through the connection of internet. The module IP address knows means anyone might see the data. Create A website considers all information any risk data means highlighting. Android app also creates install in mobile open the app see the normal and abnormal data. Abnormal data indication alert by user web page data access sees many people's means set multi-user it prevents human begin life.

LITERATURE REVIEW

In the quite a while of 2008, LIU zhen-ya, WANG Zhen-dong Furthermore chen Rong, Intelligent private security alert and remote control module dependent upon single chip Computer, the paper concentrates on, canny private robber alarm, crisis alarm, shoot alarm, poisonous gas spillage remote programmed callous alert and more remote control system, which may be dependent upon 89c51 single chip computer. The device can perform a programmed alarm, which calls the police hotline amount naturally. It can additionally make a voice alert and reveals to alert struck them deliver. This canny security system cans a chance to be utilized control that electrical force remotely through phone[12] .

In the quite a while from claiming 2008, chen Peijiang What's more Jiang Xuehhua, "Design Furthermore execution from claiming remote checking framework dependent upon GSM", this paper concentrates on the remote checking system, on account of those remote remote screening framework need additional requisitions a remote following framework In light of SMS through GSM in the quite a while from claiming 2002, k. Galatsis, w. Wlodarsla, k. Kalantar-Zadeh Also An. Trinchi,"Investigation from claiming gas sensors for vehicle lodge air nature monitoring", this paper concentrates on, auto lodge air nature following might make viably investigated utilizing metal oxide semiconducting (MOS) gas sensors. In this paper, economically accessible gas sensors need aid compared with created Moo3 built sensors pos.

Proposed System

This framework utilizing limited radiation sensor and limited gases sensor, these sensors are collect the transmitted information using Wi-Fi module to IoT module. Most dangerous area accidents occur time intimated data sending speed is high must need. IoT module using transmitting and receiving data range is high and extendable as possible. The poisonous gas and radiation or leakage monitoring process of the system marked with the importance of real-time detection and regulates the poisonous gas and radiation to automate the controlling and monitoring system for real-time utilization.



Figure.1.Block diagram

Sensors

Fire Sensor

The fire sensor circuit is excessively touchy and recognizes an ascent in temperature of 10 degrees or more in its region. Conventional flag diodes line IN 34 and OA 71 displays the property and the interior protection of these gadgets will diminish the temperature rises. In the one-sided turnaround mode, this impact will be more noteworthy. Regularly the diode can produce around 600 milli-volts at 5-degree centigrade. For every degree ascend in temperature; the diode creates 2mV yield voltage. That is at 5 degrees it is 10mV, and when the temperature ascends to 50 degrees, the diode will give 100 milli-volts. This voltage is utilized to trigger the rest of the circuit[4]. Transistor T1 is a temperature controlled switch, and its construct voltage depends in light of the voltage from the diode and from VR and R1. Regularly T1 conducts (because of the voltage set by VR) and LED gleams.

MQ2 Sensor

The MQ2 family of sensors has a tiny heater inside along with an electrochemical sensor. They react for a range of gases at the room temperature. The analog signal reads an analog input of the Arduino as the output of each sensor. The principle target of the whole framework is to recognize poisonous gas and radiation spillage[5] .

www.IJour.net
Members Copy, Not for Commercial Sale
Downloaded From IP - 18.222.125.171 on dated 29-Apr-2024

www.IJour.net
Members Copy, Not for Commercial Sale
Downloaded From IP - 18.222.125.171 on dated 29-Apr-2024

In case any poison gases or radiations exist in industry surroundings that the neighboring industry region living people mostly influence radiation or gases. Some gases continuous breathing means to kill the human being and environment mixed this gas or radiation polluted environment condition

MQ7 Gas

The "Carbon Monoxide (co) sensor" is appropriate for sensing the concentrations of CO in the air. The MQ-7 could recognize the concentrations of CO-gas anywhere from 20ppm to 2000ppm. The "MQ 7 gas sensors" inside a small[6] heater are there with an electrochemical sensor. Heater produces electrical current to Arduino board. The sensor yield is an analog signal" read by analog input pin of the ARM7.

MQ135 Gas Sensor

The conductivity of the sensor is higher alongside with the rising of gas concentration. Electro circuit, translate the change of conductivity to correspond yield signal of "gas concentration". The MQ 135 gas sensor inside a small heater is there with an electro-chemical sensor[7] . Heater produces electrical current to Arduino board. They are sensitive for a range of gas and are used indoors closed room at room temperature. The output of the sensor is an analog signal read by analog input pin of the Arduino board.

Temperature Sensor LM 35

The centigrade temperature is directly proportional to the output voltage of the temperature. The temperature is an integrated circuit which is used to measure the temperature. In our project we are using the temperature sensor series is LM35. The LM35 has an advantage that the user has not to create the conversion of Kelvin to the centigrade. The LM35 is directly in Celsius. The LM35 sequences are precision integrated-circuit temperature sensors, whose output voltage may be linearly proportional to centigrade temperature [8] . The LM35 is an advantageous element through linear temperature sensors.

Buzzer

The alert or buzzer utilizing these device principle explanations is shown to alert working people, and staying people moved to safety area to save the humans life and environment.

Internet of Things (IoT)

Data Acquisition can be achieved through the utilization of QR code, the bar code and RFID identification and sensors for taking a physical measurement in the device. The networking of IoT technology is a much larger topic that can be addressed in our available time[9].

The proposed system contains the ESP8266 is the Wi-Fi module which is connected to the server. The tiny module allows the microcontroller to connect Wi-Fi network and make a simple TCP/IP connection.



Figure.2. Internet of Thing

WI-FI

Wi-Fi is short name for wireless reliability. By and large, Wi-Fi alludes to an IEEE 802. 11 Wireless Local Area Network (WLAN). All the more particularly, Wi-Fi will be the business standard for things as characterized by the Wi-Fi[10] Alliance and complying with IEEE 802. 11 standards.

Sensors continuously monitor the gases in the encompassing and posts into the server for storing and use of information in future. Although continuously monitoring if any gas level surpasses the range to that of the normal range in the air the alert will be improved, and an SMS notice will be presented on safety control board of the organization and even to the workers mobile station only if necessary. Figure 5 shows the syntax of the parameter (maximum permissible value) = value detected at the moment. If value identified at that specific moment is higher than that of the maximum tolerable amount, an SMS has sent towards imitating the GMS module through commands programmed in the microcontroller.

RESULTS

The display has been reenacted by utilizing by Proteus Software to screen the noxious gas and radiation

location utilizing distinctive sensors. The adjustment in, carbon monoxide, smelling salts, radiation, methane will be recognized by separate sensors and can be resolved. Figure 4 shows the prototype for the system design. Figure 5 shows the SMS notified when harmful gases levels have been raised from a normal level to harmful level. Fig6 shows the values of gases that are continuously detected by the sensors having a temperature sensor is an added minimum requirement besides gas sensor.



Figure.3. Hardware Experimental Setup

Figure.4. Results in IOT

The above results show the outputs seen when the module detects the difference in the normal conditions as per given and saved conditions in the module and alerts the system about the changes.

www.IJour.net
Members Copy, Not for Commercial Sale
Downloaded From IP - 18.222.125.171 on dated 29-Apr-2024



Figure.5. Results in application

The file chart 1 shows the temperature readings where the x-axis shows the time and the y-axis shows the temperature changes in the area. In the same way the filechart2 and filechart4 shows the butane and co_2 gases diffusion respectively. In them the x axis shows the time readings and the y-axis shows the range of diffusion.

CONCLUSION

In this work, an intelligent system for toxic gas and radiation discovery checking cautioning has been created to defeat the drawback looked at more established techniques by utilizing Wi-Fi module and web of things. Consequently, the utilization of serial correspondence makes the system with the Arduino controller and IoT. The IoT door associate remote sensor connects with the web, guarantee the operation of the gas and alcohol observing framework. It utilized just constrained sensor. The created application used additionally for checking gas and radiation in android portable.

Conflict of Interest: Nil

Source of Funding: Self

Ethical Clearance: My research article what we have written is completely self depended which enrolls complete research depended on the prototype of each individual so it doesn't match any other research proposals/research persons.

REFERENCES

1. Chang-Su Ryu. IoT-based Intelligent for Fire Emergency Response Systems. International Journal

of Smart Ho me. 2015; l. 9,(3): p. 161 -168.

2. Guohong Li, Wenjing Zhang, Yi Zhang A Design of the IOT Gate way for Agricultura l Greenhouse" Sensors & Transducers. 2014; 172(6): p. 75-80.
3. JinfengSuna The intelligent crude oil anti-theft system based on IoT under different scenarios 20th International Conference on Knowledge Based and Intelligent Information and Engineering Systems, KES. 2016, 5 -7, York, Kingdom.
4. JebahJayKu mar. AbishlinBlessy Secure Smart Environment Using IOT based on RFID. International Jo urnal of ComputerScienc e and Informat ion Technologies, 2014 ; 5 (2): P 2493-2496.
5. Kumar.A .Application of Gas Monitoring Sensors in Underground Coal Mines and Hazardous Areas. International Journal ofComputer Technology and Electronics Engineering (IJCTEE). 2013; 3 (3).
6. Suresh Kumar. Integration of Wireless Sensor Network with Virtual instrumentation in a Ha zardous Environ mental.2014; l.2(4).
7. Bhavana Godavarthi[1], Papa RaoNalajala, M Lakshmi Ravi Teja.Wireless Sensors Based Data Acquisition System Using Smart Mobile Application.International Journal of Advanced Trends in Computer Science and Engineering, 2016 ;5 (1): p.25-29.
8. vishwajeet "A Survey on the Smart Ho mes using Internet of Things (IOT)"International journal of Advance Research incomputer science and management studies .volume 2, Issue 12, December 2014.
9. P. Dayaker, Y. Madan Reddy and M Bhargav Kumar, A Survey on Applications and Security Issues of Internet of Things (IoT), International Journal of Mechanical Engineering and Technology , 8(6), 2017, pp. 641–648.
10. Bhavana Godavarthi, Paparao Nalajala," Design and Implementation of Vehicle Navigation System in Urban Environments using Internet of Things (IoT)", IOP Conf. Series: Materials Science and Engineering 225 (2017) 012262.
11. Kaleel Ahmed A and Prof. Dr. C.B. Senthil Kumar, Correlating Internet of Things. International Journal of Management, 8 (2), 2017, pp. 68–76.
12. Paparao Nalajala, BhavanaGodavarthi,"Working Women Hand Held Safety Self Defense System using IoT", Journal of Advanced Research in Dynamical and Control Systems, 18-Special Issue, Year: 2017, Pages::2051-2059.

www.IJour.net
Members Copy, Not for Commercial Sale
Downloaded From IP - 18.222.125.171 on dated 29-Apr-2024